



GF-4200R

Analog Addressable FACP, 2 SLCs, Red Enclosure

GF-4200B

Analog Addressable FACP, 2 SLCs, Beige Enclosure

Phone: 888- 673-2900 • Local: 309-755-6352 • Fax: 309-755-8310 • email: inquire@globalfirecontrol.com

DESCRIPTION

The G-Force 4200 series panels are high quality, modularly constructed, conventional &/or analog/addressable technology, stand-alone or networking, fire alarm control panels.

The GF-4200 comes with 2 SLCs on the main control board and has expansion capabilities of up to 8 SLCs on one system. Each additional SLC card has 2 circuits on them, up to 3 SLC card expansions per system. The G-Force 4200 panel utilizes Apollo's advanced intelligent protocol called "Discovery" and also Apollo's XP-95 series devices. One SLC can operate 126 devices, mixing or matching detectors and modules.

In addition to the addressable SLC loops, the system can handle up to 6 conventional input zone cards, either 10 class "B" or 5 class "A" zones per card.

The GF-4200 architecture allows the expansion cards to be remotely mounted for ease of installation. Each expansion card can be mounted in its own separate cabinet and connected back to the GF-4200 via a pair of wires.

The GF-4200 system can have up to 15 remote annunciators connected to the on board RS485 annunciator port. It can also connect 63 more GF-4200 panels in a network configuration, 64 panels maximum (UL Pending).

The G-Force 4200 series FACP tailors to technicians with remote diagnostic features allowing the ESD to trouble shoot the panel from his office before he dispatches a technician to the site. Auto programming also provides technicians with quick, system specific (devices), databases with just a few keystrokes.

Automatic drift compensation provides a high level of reliability to building owners by allowing detectors to self compensate for changing environments. Some additional features beneficial to building owners are: day/night sensitivity modes; holiday scheduling for up to 20 holidays; alarm verification; and much more.



GF-4200R

FEATURES

- UL listed (File# UOJZ.S24284)
- COA (Certificate of Approval) NYC File #6012
- Modular design
- Conventional &/or Analog/Addressable technology
- Automatic Drift Compensation
- Expandable from 2 to 8 SLCs
- Expandable to 60 conventional zones
- 15 Annunciators per panel
- Networking up to 64 Nodes
- Auto-programming & remote programming
- Panel mounted or remote cabinet mounted SLC cards (up to 6,000 ft. away from the panel)
- 1,008 point capacity per panel
- 64,512 point capacity per network
- 250 software zones
- Alarm Verification
- Optional remote trouble shooting capability
- Day/night sensitivity adjustments
- Flash LED option
- 160 Character LCD read-out w/back-lighting



ORDERING INFORMATION

Model No.	Description
GF-4200R	Analog/Addressable FACP, 2 SLCs class A or B, 4 NACs class A or B, Red enclosure
GF-4200-LC	2 SLC expansion board, class A or B
GF-4200-CZ10	10 conventional zone expansion board, 10 class B or 5 class A
GF-4200-LCD	Remote LCD annunciator, 160 characters (8 lines x 20 characters), in Red enclosure
GF-4200-RC	Relay module expansion card
GF-4200-RCCBL	Relay module expansion cable
GF-4200-EXP	Expansion cabinet for LC or CZ10 cards, holds 2 cards + 2 GF-4200-RC cards
GF-4200-EXP5	Expansion cabinet for LC or CZ10 cards, holds 2 cards + 5 GF-4200-RC cards
GF-4200-MOD	Modem for remote programming
GF-4200-CAM	Communications adapter module, used for PC programming

SPECIFICATIONS

Primary AC: (Optional 220VAC)	120VAC @ 2 Amps 60 Hz	Max. Charger Current:	1.7 Amps
Output DC:	24VDC @ 7 Amps	NAC Outputs:	(4) 2.0 Amp @ 24VDC (Class A or B)
Power Supply:	7 Amp Integrated	Aux. Power:	500mA @ 24VDC
Dimensions:	14.5"W x 25"H x 4"D	Relay Outputs:	(2) Form C 1 Amp @ 30VDC
Weight:	30 lbs. (without batteries)	Voltage Outputs:	(2) 500mA @ 24VDC
Color:	Red (optional Beige)	PC Port:	RS232
Material:	ABS/Steel Enclosure	Printer Port:	RS232
SLC Loops:	2, expandable to 8 (Class A or B)	Network:	Dual RS485 Ports (64 Panels Max.)
Devices per Loop:	126 Sensors & Modules)	Zones:	250 Software Zones per System
Display:	8 Line x 20 Character LCD (160 Characters total)		



GLOBAL FIRE CONTROL, INC.

1201 7th Street, Suite 103
East Moline, IL 61244

Phone: 888-673-2900
Local: 309-755-6352
Fax: 309-755-8310

email: inquire@globalfirecontrol.com

NOTICE: The information contained in this document is intended only as a summary and is subject to change without notice. The devices described in this document have specific instruction sheets, which cover various technical limitation and liability information. Copies of these instruction sheets and the General Product Warning and Limitations Document, which also contains important information are provided with the product and are available from Global Fire Control, Inc. Information contained in these documents should be consulted before specifying or using the product. For further information or assistance concerning particular problems contact Global Fire Control, Inc. Global Fire Control, Inc. reserves the right to change specifications without notice.